



**CUMMINS INC.**  
Columbus, IN 47201  
Marine Performance Curves

Basic Engine Model

**QSC8.3-600 HO**

Curve Number:

**M-94339**

Engine Configuration

**D413038MX03**

CPL Code:

**0906**

Date:

**9-Aug-13**


Displacement: **8.3 liter** [505 in<sup>3</sup>]      Rated Power: **442 kw** [593 bhp, 600 mhp]  
 Bore: **114 mm** [4.49 in]      Rated Speed: **3000 rpm**  
 Stroke: **135 mm** [5.31 in]      Rating Type: **High Output**  
 Fuel System: **HPCR**      Aspiration: **Turbocharged / Sea Water Aftercooled**  
 Cylinders: **6**

CERTIFIED: This diesel engine complies with or is certified to the following agencies requirements:

EPA Tier 3 - Model year requirements of the EPA marine regulation (40CFR1042)

IMO Tier II - Tier 2 (Two) NOx requirements of International Maritime Organization (IMO), MARPOL 73/78 Annex VI, Regulation 13

RCd - meets the requirements of the Recreational Craft Directive 94/25/EC as amended by 2003/44/EC in accordance with ISO 8178-1



Speed	Full Throttle- Power		Full Throttle- Torque		Fuel Cons.- Prop. Curve 2.7 Exp.	
	rpm	kw (hp)	N·m (ft·lb)	L/hr (gal/hr)		
3065	442	(593)	1377	(1016)		
3000	442	(593)	1407	(1038)	123.1	(32.5)
2800	427	(573)	1457	(1075)	103.3	(27.3)
2600	418	(561)	1536	(1133)	79.4	(21.0)
2400	410	(549)	1630	(1202)	64.1	(16.9)
2200	398	(534)	1727	(1274)	50.4	(13.3)
1800	339	(455)	1799	(1327)	31.0	(8.2)
1600	291	(390)	1735	(1280)	22.4	(5.9)
1400	179	(240)	1223	(902)	14.2	(3.7)
1200	110	(147)	874	(645)	11.1	(2.9)
1000	79	(105)	750	(553)	7.5	(2.0)
900	64	(86)	683	(504)	6.0	(1.6)
800	52	(69)	617	(455)	4.9	(1.3)
600	34	(46)	542	(400)	1.0	(0.3)

\* Cummins Full Throttle Requirements:

- Engine achieves or exceeds rated rpm at full throttle under any steady operating condition
- Engines in variable displacement boats (such as pushboats, tugboats, net druggers, etc.) achieve no less than 100 rpm below rated speed at full throttle during a dead push or bollard pull
- Engine achieves or exceeds rated rpm when accelerating from idle to full throttle

Rated Conditions: Ratings are based upon ISO 15550 reference conditions; air pressure of 100 kPa [29.612 in Hg], air temperature 25deg. C [77 deg. F] and 30% relative humidity. Power is in accordance with IMCI procedure. Member NMMA. Unless otherwise specified, tolerance on all values is +/-5%.

Full Throttle curve represents power at the crankshaft for mature gross engine performance corrected in accordance with ISO 15550. Propeller Curve represents approximate power demand from a typical propeller. Propeller Shaft Power is approximately 3% less than rated crankshaft power after typical reverse/reduction gear losses and may vary depending on the type of gear or propulsion system used.

Fuel Consumption is based on fuel of 35 deg. API gravity at 16 deg C [60 deg. F] having LHV of 42,780 kJ/kg [18390 Btu/lb] and weighing 838.9 g/liter [

High Output (HO): Intended for use in variable load applications where full power is limited to one hour out of every eight hours of operation. Also, reduced power must be at or below 300 rpm of the maximum rated rpm. This power rating is for pleasure/non-revenue generating applications that operate 500 hours per year or less.

CHIEF ENGINEER



# Propulsion Marine Engine Performance Data

Curve No. M-94339  
 DS : 3075  
 CPL : 0906  
 DATE: 9-Aug-13

## Air System<sup>1</sup>

Intake Manifold Pressure .....	kPa [in Hg]	230 [68]
Intake Air Flow .....	l/sec [cfm]	580 [1230]
Heat Rejection to Ambient .....	kW [Btu/min]	37 [2124]

## Exhaust System<sup>1</sup>

Exhaust Gas Flow .....	l/sec [cfm]	1336 [2830]
Exhaust Gas Temperature (Turbine Out) .....	°C [°F]	510 [950]
Exhaust Gas Temperature (Manifold) .....	°C [°F]	705 [1300]

## Emissions (in accordance with ISO 8178 Cycle E3)

NOx (Oxides of Nitrogen) .....	g/kw-hr [g/hp-hr]	4.76 [3.55]
HC (Hydrocarbons) .....	g/kw-hr [g/hp-hr]	0.20 [0.15]
CO (Carbon Monoxide) .....	g/kw-hr [g/hp-hr]	0.61 [0.45]
PM (Particulate Matter) .....	g/kw-hr [g/hp-hr]	0.09 [0.07]

## Emissions (in accordance with ISO 8178 Cycle E5)

NOx (Oxides of Nitrogen) .....	g/kw-hr [g/hp-hr]	4.68 [3.49]
HC (Hydrocarbons) .....	g/kw-hr [g/hp-hr]	0.20 [0.15]
CO (Carbon Monoxide) .....	g/kw-hr [g/hp-hr]	0.73 [0.54]
PM (Particulate Matter) .....	g/kw-hr [g/hp-hr]	0.09 [0.07]

## Cooling System<sup>1</sup>

Sea Water Pump Specifications .....	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option) .....	kPa [psi]	103 [15]

## Engines without Low Temperature Aftercooling (LTA )

### Sea Water Aftercooled Engine (SWAC)

Coolant Flow to Engine Heat Exchanger .....	l/min [gal/min]	473 [125]
Standard Thermostat Operating Range (Start to Open) .....	°C [°F]	71 [160]
Standard Thermostat Operating Range (Full Open) .....	°C [°F]	81 [178]
Heat Rejection to Engine Coolant <sup>3</sup> .....	kW [Btu/min]	270 [15345]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

- <sup>1</sup> Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.
- <sup>2</sup> No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.
- <sup>3</sup> Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.
- <sup>4</sup> Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.
- <sup>5</sup> May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC  
 COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://marine.cummins.com/>