




clarion® |  **MARINE AUDIO**
PRODUCT CATALOG



LET'S HEAR IT.

*The driving beat of a kick drum, the snap of a snare,
the wail of your favorite guitarist's most powerful solo,
the unmistakable sound of a vocalist's art...
It's all there with a Clarion Marine Audio system.*

SOURCE UNITS

Your tech meets ours... and beautiful music happens.



All Clarion Marine Source Units are certified for real marine duty!

- Meet or exceed ASTM B117 (Salt Fog Exposure).
- Meet or exceed ASTM D4329 (UV Exposure).
- Coated circuit boards resist corrosion in marine environments.
- Minimal power consumption when powered off, to conserve your batteries.



GR10BT

DIGITAL MEDIA RECEIVER

- Global, digital AM/FM tuner, plus NOAA weather radio (US only)
- Wireless Bluetooth® audio streaming
- MP3/WMA USB File Playback, with 1.1A charging output (rear USB port)
- One stereo pair of auxiliary inputs
- Built-In Amplifier: 4 x 16W RMS @ 4 ohms
- Four 2V RCA outputs (Front + Rear or Sub)
- 3-Band Equalizer (Bass/Mid/Treble), plus seven EQ presets
- Subwoofer Low Pass Filter (80/120/160 Hz)
- Easy-to-read, high-contrast, segmented LCD display and illuminated keypad
- 4-inch outside diameter, 3-inch mounting hole
- Water Resistant: IPX5 (front), IPX3 (rear)



M508

DIGITAL MEDIA RECEIVER

- Global, digital AM/FM tuner, plus NOAA weather radio (US only)
- Wireless Bluetooth® audio streaming with aptX® audio
- MP3/WMA USB File Playback, with 1A charging output (front USB port)
- SiriusXM-Ready® (SiriusXM® Connect tuner and antenna sold separately)
- Pandora® Radio ready via your iPhone®
- Auxiliary Audio RCA Input (front)
- Built-In Amplifier: 4 x 18W RMS @ 4 ohms
- Eight 4V RCA outputs (Front/Rear/Sub/Fixed)
- 3-Band Equalizer (Bass/Mid/Treble), plus eleven EQ presets
- Subwoofer Low Pass Filter (80/120/180 Hz)
- Easy-to-read, high-contrast, 2-line, segmented LCD display and illuminated keypad
- Standard DIN Chassis and Faceplate
- Not Water Resistant



M608

DIGITAL MEDIA RECEIVER

- Global, digital AM/FM tuner, plus NOAA weather radio (US only)
- Wireless Bluetooth® audio streaming with aptX® audio
- MFI for Apple iPod/iPhone® USB Connectivity
- MP3/WMA USB File Playback, with 2.1A charging output (rear USB port)
- SiriusXM-Ready® (SiriusXM® Connect tuner and antenna sold separately)
- Pandora® Radio ready via your iPhone®
- Dual Auxiliary Audio RCA Inputs (rear)
- Built-In Amplifier: 4 x 18W RMS @ 4 ohms
- Eight 4V RCA outputs (4 independent zones)
- 3-Band Equalizer (Bass/Mid/Treble)
- Subwoofer Low Pass Filter (60/90/120 Hz)
- Easy-to-read, high-contrast, 2-line, segmented LCD display and illuminated keypad
- Standard DIN Chassis with 1.5 DIN Faceplate
- Drop-in replacement for CMD6, CMD7, CMD8 or CMV-1 Clarion Marine Source Units.
- Water Resistant: IP55 (front), IPX3 (rear)



CMM-10

COMPACT MARINE SOURCE UNIT WITH LCD DISPLAY

- Weatherproof (IP66 rated) design and construction
- Ultra-bright, 2.09-inch (53 mm) LCD display with dim control
- Intuitive interface with large text
- Easy-to-use, single rotary control and backlit buttons
- Global AM/FM Tuner with RDS (Radio Data System) display info, where available.
- Wireless Bluetooth® audio streaming
- USB 2.0 input with 1A charging
- Built-in 80 watt Amplifier: 4 x 20W RMS @ 4 ohms
- 4-channel preamp (1.5V RMS) outputs with selectable Zone 2 or subwoofer functionality
- Onboard tone (Bass/Treble) controls, plus independent Subwoofer zone level control
- Ultra-compact chassis suitable for small watercraft, powersports and golf cart applications



CMM-20

MARINE SOURCE UNIT WITH LCD DISPLAY

- Weatherproof (IP66 rated) design and construction
- Ultra-bright, 2.37-inch (60 mm) LCD display with dim control
- Intuitive interface with large text
- Large, easy-to-use rotary control and backlit buttons
- Global, digital AM/FM tuner with RDS (Radio Data System) display info, plus NOAA weather radio (US only)
- Wireless Bluetooth® audio streaming
- USB 2.0 input with 1A charging
- One stereo pair of auxiliary inputs (2V RMS)
- 2-channel preamp (1.5V RMS) outputs with selectable Zone 2 or subwoofer functionality
- Built-in 100 watt Amplifier: 4 x 25W RMS @ 4 ohms
- Onboard tone (Bass/Treble) controls or selectable 4 preset equalizer



CMM-30

MARINE SOURCE UNIT WITH FULL-COLOR LCD DISPLAY

- Weatherproof (IP66 rated) design and construction
- Ultra-bright, 3-inch (76 mm) full-color LCD display with dim control
- Intuitive interface with large text
- Large, easy-to-use rotary control and backlit buttons
- Global, digital AM/FM tuner with RDS (Radio Data System) display info, plus NOAA weather radio (US only)
- SiriusXM-Ready® (tuner, antenna, and subscription sold separately)
- Wireless Bluetooth® audio streaming
- USB 2.0 input with 2.1A charging
- One stereo pair of auxiliary inputs (2V RMS)
- Master volume control over four separate audio zones, each with independent features/settings (Level Control, HP Xover, Rename Zone and Volume Limit)
- 8-channel preamp (3.5V RMS) outputs with selectable Zone 4 or subwoofer functionality
- Built-in 100 watt Amplifier: 4 x 25W RMS @ 4 ohms
- Customizable, built-in 5-band equalizer or onboard tone controls (Bass/Mid/Treble)
- NMEA 2000® Certified for control functionality via existing vessel networks. Compatible MFDs include Garmin, Lowrance and Simrad (Refer to MFD manufacturer for device compatibility info.)



CMM-30BB

HIDEAWAY MARINE SOURCE UNIT

- Weatherproof (IP66 rated) design and construction
- Intuitive interface with large text
- Global, digital AM/FM tuner with RDS (Radio Data System) display info, plus NOAA weather radio (US only)
- SiriusXM-Ready® (tuner, antenna, and subscription sold separately)
- Wireless Bluetooth® audio streaming
- High-speed, USB 2.0 input with 2.1A charging output
- One stereo pair of auxiliary inputs (2V RMS)
- Master volume control over four separate audio zones, each with independent features/settings (Level Control, HP Xover, Rename Zone and Volume Limit)
- 8-channel preamp (3.5V RMS) outputs with selectable Zone 4 or subwoofer functionality
- Built-in 100 watt Amplifier: 4 x 25W RMS @ 4 ohms
- Customizable, built-in 5-band equalizer or onboard tone controls (Bass/Mid/Treble)
- NMEA 2000® Certified for control functionality via existing vessel networks. Compatible MFDs include Garmin, Lowrance and Simrad (Refer to MFD manufacturer for device compatibility info.)





SPEAKERS & SUBWOOFERS

A great day on the water just got even better.



All Clarion Marine Speakers are certified for real marine duty!

- Meet or exceed ASTM B117 (Salt Fog Exposure).
- Meet or exceed ASTM D4329 (UV Exposure).
- Marine-grade materials and finishes
- Corrosion-resistant connections

PREMIUM



CMSP-651-SWG

6.5-INCH PREMIUM MARINE COAXIAL SPEAKERS

- Salt & Sun Certified
- Bridge-mounted, 1-inch (25 mm), edge-driven, silk dome tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Injection-molded woofer cone bodies and marine-grade suspension components
- Standard cutout size and screw hole pattern for easy retrofitting
- 50W RMS power handling, great for source-unit powered systems, even better with Clarion Marine amplifiers
- Waterproof Speaker Connectors
- Includes both White & Metallic Gray Sport Grilles



CMSP-651RGB-SWG

6.5-INCH PREMIUM MARINE COAXIAL SPEAKERS WITH RGB LIGHTING

- Salt & Sun Certified
- Built-In RGB LED Lighting
- Bridge-mounted, 1-inch (25 mm), edge-driven, silk dome tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Injection-molded woofer cone bodies and marine-grade suspension components
- Standard cutout size and screw hole pattern for easy retrofitting
- 50W RMS power handling, great for source-unit powered systems, even better with Clarion Marine amplifiers
- Waterproof Connectors for Speaker & LED Illumination
- Includes both White & Metallic Gray Sport Grilles



CMSP-771RGB-SWG

7.7-INCH PREMIUM MARINE COAXIAL SPEAKERS WITH RGB LIGHTING

- Salt & Sun Certified
- Built-In RGB LED Lighting
- Bridge-mounted, 1-inch (25 mm), edge-driven, silk dome tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Injection-molded woofer cone bodies and marine-grade suspension components
- 7.7-inch woofer delivers more output and stronger bass, compared to the 6.5-inch model
- 60W RMS power handling, great for source-unit powered systems, even better with Clarion Marine amplifiers
- Waterproof Connectors for Speaker & LED Illumination
- Includes both White & Metallic Gray Sport Grilles



CMSP-101RGB-2 or CMSP-101RGB-4

10-INCH INFINITE BAFFLE MARINE SUBWOOFER WITH RGB LIGHTING

- Salt & Sun Certified
- Built-In RGB LED Lighting
- Long-excursion, high power handling design delivers low-distortion and excellent low frequency capability
- Optimized for infinite baffle applications, without requiring a dedicated enclosure
- Waterproof Connectors for Subwoofer & LED Illumination
- 250W RMS power handling, ideally matched to the Clarion Marine subwoofer amplifier
- Sold Individually, without Grille, in single 2 ohm or 4 ohm voice coil models, for maximum versatility

STANDARD



CMS-651-CWB

6.5-INCH MARINE COAXIAL SPEAKERS WITH CLASSIC GRILLES

- Salt & Sun Certified
- Bridge-mounted, 0.50-inch (13 mm) balanced-dome, polymer tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Vacuum-formed polymer woofer cone bodies and marine-grade suspension components
- Standard cutout size and screw hole pattern for easy retrofitting
- Includes both White & Black Classic Grilles
- 30W RMS power handling, perfect for source unit-powered systems



CMS-651-SWB

6.5-INCH MARINE COAXIAL SPEAKERS WITH SPORT GRILLES

- Salt & Sun Certified
- Bridge-mounted, 0.50-inch (13 mm) balanced-dome, polymer tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Vacuum-formed polymer woofer cone bodies and marine-grade suspension components
- Standard cutout size and screw hole pattern for easy retrofitting
- Includes both White & Black Sport Grilles
- 30W RMS power handling, perfect for source unit-powered systems



CMS-651RGB-SWB

6.5-INCH MARINE COAXIAL SPEAKERS WITH SPORT GRILLES AND RGB LIGHTING

- Salt & Sun Certified
- Built-In RGB LED Lighting
- Bridge-mounted, 0.50-inch (13 mm) balanced-dome, polymer tweeter with 2nd order, high-pass filter, integrated within the woofer basket
- Vacuum-formed polymer woofer cone bodies and marine-grade suspension components
- Standard cutout size and screw hole pattern for easy retrofitting
- Waterproof Connectors for Speaker & LED Illumination
- Includes both White & Black Sport Grilles
- 30W RMS power handling, perfect for source unit-powered systems



CMSP-101RGB Subwoofer shown with CMGP-101-SG Premium 10 in / 250 mm Marine Subwoofer Sport Grille in Metallic Gray finish



CMGP-101-SW or CMGP-101-SG

10-INCH MARINE SUBWOOFER GRILLE

- Salt & Sun Certified
- White or Metallic Gray (sold individually)
- Subwoofer grilles match the color and styling of the Premium marine coaxial speakers





AMPLIFIERS

The power you need for full throttle magic.



All Clarion Marine Amplifiers are certified for real marine duty!

- Meet or exceed ASTM B117 (Salt Fog Exposure).
- Meet or exceed ASTM D4329 (UV Exposure).
- Meet or exceed 3.0G of vibration resistance.
- Marine-grade, hard anodized aluminum chassis
- Coated circuit boards resist corrosion in marine environments.
- Efficient Class D design & minimal power-off current draw conserves battery power.



XC2510

FIVE-CHANNEL SYSTEM AMPLIFIER

- Powers a complete four speaker plus subwoofer system.
- Efficient Class D technology
- Rated Power (1% THD+N, 14.4V):
50W x 4 + 200W x 1 @ 4 ohms
75W x 4 + 300W x 1 @ 2 ohms
- Frequency Response:
15-30kHz (Ch. 1-4)
15-250Hz (Ch. 5)
- ≥ 70dB S/N Ratio
- 15-250Hz Variable 12dB/Oct High-Pass Filter (Ch. 1-4)
- 35-250Hz Variable 12dB/Oct Low-Pass Filter (Ch. 5)
- Variable Bass Boost (Ch. 5)
0-12 dB @ 50Hz
- 6-ch RCA Low Level Inputs
- 4-ch High Level Inputs
- Double layer PCB, coated for corrosion protection
- Dimensions (H x W x D):
1.54 x 11.02 x 4.33 in.
(39 x 280 x 110 mm)



XC2410

4-CHANNEL AMPLIFIER

- Powers four speakers, or two speakers plus a subwoofer.
- Efficient Class D technology
- Rated Power (1% THD+N, 14.4V):
50W x 4 @ 4 ohms
75W x 4 @ 2 ohms
150W x 2 @ 4 ohms (bridged)
- Frequency Response: 15-30kHz
- ≥ 70dB S/N Ratio
- 15-250Hz Variable 12dB/Oct High-Pass Filter, for each channel pair
- 4-ch RCA Low Level Inputs
- 4-ch High Level Inputs
- Double layer PCB, coated for corrosion protection
- Dimensions (H x W x D):
1.54 x 7.17 x 3.23 in.
(39 x 182 x 82 mm)



XC2110

MONO SUBWOOFER AMPLIFIER

- Easily drives one subwoofer (2 ohms or 4 ohms), or two subwoofers (4 ohms each).
- Efficient Class D technology
- Rated Power (1% THD+N, 14.4V):
200W x 1 @ 4 ohms
300W x 1 @ 2 ohms
- 15-250Hz Frequency Response
- ≥ 70dB S/N Ratio
- 35-250Hz Variable 12dB/Oct Low-Pass Filter (Ch. 5)
- Variable Bass Boost
0-12 dB @ 50Hz
- 2-ch RCA Low Level Inputs
- 2-ch High Level Inputs
- Double layer PCB, coated for corrosion protection
- Dimensions (H x W x D):
1.54 x 7.85 x 3.23 in.
(39 x 199 x 82 mm)



XC2510 Control Panel





REMOTES & ACCESSORIES

Control it all, from just about anywhere.



*Features and functionality vary by Clarion source unit. Please visit our website for details regarding Clarion source unit and 3rd party MFD compatibility.



CMR-30 MARINE WIRED REMOTE WITH FULL-COLOR LCD DISPLAY

- Enjoy full-function control of your source unit from auxiliary locations
- Weatherproof design (IP67 rated) with full-color, 3-inch (76 mm) LCD display
- Connects directly to your source unit using accessory remote cables and splitters (sold separately): 25 ft. Marine Remote Cable (CMC-RC-25), 6 ft. Marine Remote Cable (CMC-RC-6), and Marine Remote Y-Cable (CMC-RC-Y)
- Add up to three remotes, up to 75 ft. (22.8 m) away (cumulative) from your source unit
- Compatible with CMM-30 and CMM-30BB



CMR-20 MARINE WIRED REMOTE WITH LCD DISPLAY

- Enjoy full-function control of your source unit from auxiliary locations
- Weatherproof design (IP67 rated) with ultra-bright, 2.44-inch (62 mm) LCD display
- Connects directly to your source unit using accessory remote cables and splitters (sold separately): 25 ft. Marine Remote Cable (CMC-RC-25), 6 ft. Marine Remote Cable (CMC-RC-6), and Marine Remote Y-Cable (CMC-RC-Y)
- Add up to three remotes, up to 75 ft. (22.8 m) away (cumulative) from your source unit
- Compatible with CMM-20, CMM-30 and CMM-30BB



CMR-10 ROUND, MARINE WIRED REMOTE (NO DISPLAY)

- Enjoy auxiliary control of frequently used source unit functions, including power on/off, source select, volume up/down, mute/unmute, pause/resume, track control, fast-forward/fast-rewind, preset up/down
- Weatherproof design (IP67 rated) with backlit buttons
- Mounts with just a single hole (2 in. / 50 mm)
- Connects directly to your source unit using accessory remote cables and splitters (sold separately): 25 ft. Marine Remote Cable (CMC-RC-25), 6 ft. Marine Remote Cable (CMC-RC-6), and Marine Remote Y-Cable (CMC-RC-Y)
- Add up to three remotes, up to 75 ft. (22.8 m) away (cumulative) from your source unit
- Compatible with CMM-20, CMM-30 and CMM-30BB



CMR-L1 RGB LIGHTING CONTROLLER

- Controls the lighting mode, color, brightness and other settings for RGB LED-equipped speakers, subwoofers and accessories. Up to 15 meter (49.2 ft) operating range and maximum 2 amp output capacity. Includes wireless (433.92 MHz) remote and CR2025 (3V) battery.



AUDIO CABLES

Marine-grade audio cables are ideal for connecting your source unit to a Clarion marine amplifier.

- Twisted-pair construction rejects noise.
- Marine-grade brass connector elements with sealed connector bodies, for corrosion resistance
- Tinned OFC copper conductors

CMC-GRYAIC2-3
2-ch Marine Audio Interconnect, 3 ft./0.91 m

CMC-GRYAIC2-6
2-ch Marine Audio Interconnect, 6 ft./1.83 m

CMC-GRYAIC2-18
2-ch Marine Audio Interconnect, 18 ft./3.66 m



CMC-GRYAIC2-1F2M
Marine Audio Y-Adaptor with 1 female jack/2 male plugs



CMC-GRYAIC2-1M2F
Marine Audio Y-Adaptor with 1 male plug/2 female jacks



CMC-USBIX-PNL

PANEL JACKS

Weatherproof panel-mounting jacks create convenient connection points for a variety of portable devices.

CMC-USBIX-PNL
9-pin USB 2.0/3.0 Port

CMC-USBCHG/2X-PNL
Dual USB Charging Port

CMC-3.5MM-PNL
3.5 mm Mini Audio Jack (stereo)

CMC-USB/3.5MM-PNL
9-pin USB 2.0/3.0 Port, plus 3.5 mm Mini Audio Jack (stereo)



CMC-3.5MM-PNL



CMC-USBCHG/2X-PNL



CMC-USB/3.5MM-PNL



CMC-RC-6

REMOTE CABLES

For compatible CMM source unit models

CMC-RC-6
6 ft./1.83 m Remote Extension Cable

CMC-RC-25
25 ft./7.6 m Remote Extension Cable

CMC-RC-Y
Remote Y-Adaptor, 1 Male Plug, 2 Female Jacks

For legacy source unit models (M508 and M608)

MWRYC-RET
1-Male to 2-Female splitter

MWRXC-RET
25 ft./7.6 m Extension Cable



CMC-RC-25



MWRYC-RET



MWRXC-RET



CMC-RC-Y



CMC-WHTANT-AM/FM
Motorola Style AM/FM Antenna



IT'S TIME TO WORK ON YOUR PLAYLISTS.
Your authorized Clarion Marine dealer can take care of the rest.

LET'S HEAR IT.



To find your nearest authorized dealer, visit our website or call:

1-800-GO-CLARION (1-800-462-5274)

www.clarionmarine.com



10369 North Commerce Parkway, Miramar, FL 33025 USA